

COVERBIND

CPB3SGCFC

PERFECT BINDER

Item #: 04TPTC55700C

Bookbinding has never been easier with the Coverbind CPB3SGCFC Perfect Binder with Side Gluing, Cover Feeder, and Creaser. Its functional design makes it ideal for medium to large volume binding, and its simple operation is an added bonus. The machine is equipped with an automatic cover feeder with creaser and a vertical stacker to increase productivity. The two separate glue tanks and rollers evenly apply adhesive to the main cover and the spine of the book.

Adjust the book's thickness by simply turning the lever dial to the right to angle the book or to the left to round it. By lifting the cover and adjusting it up and down, the spine position of the book can also be adjusted. The scraping and milling system on this binding machine ensures that coated, oil-infused, and UV coated materials adhere. It also has a vacuum system that collects dust and other debris after the book spine is cut, keeping your machine and workspace clean. This machine stacks completed books vertically in a loading box for the convenience of the operator.

Start binding premium soft cover books, novels, manuals, and more, on-demand with the Coverbind CPB3SGCFC Perfect Binder with Side Gluing.

Key Benefits & Features:

- **Fast Binding** - Bind up to 360 books per hour, depending on the book specifications and operator capabilities.
- **Efficient Controls** - A simple control panel lets you customize the machine to your specific job quickly.
- **Automated Clamping** - A pneumatic powered clamping mechanisms automatically adjusts to your book block thickness up to 2".
- **Optimum Glue Penetration** - Milling and scraping rougher ensures maximum glue penetration and finished book strength.
- **Specialized Nipping** - Set the nipper to produce an exceptionally square-backed book with an adjustable height and dwell time up to 3 seconds.
- **Stronger Bind** - Side gluing on the rear of the spine makes for exceptional finishing.
- **Saturated Glue Coverage** - Gluing rollers saturate and rollers smooth the glue to the optimum thickness.



Specifications

Maximum Speed	Up to 360 books/hour
Maximum Book Thickness	2.25" (57mm)
Maximum Cover Size	13.4" x 30.75" (34 x 78cm)
Maximum Spine Length	12.5" (32cm)
Book Block Size	12.5" x 8.7" (32cm x 22cm)
Display	LCD Screen
Clamp	Automatic/Pneumatic
Roughing Blade	Milling & 2 Heavy Duty Notching Pins
Rollers	2 Glue, 1 Metering, Side Glue Tank
Dimensions (L X W X H)	70-1/2"L x 33 W x 50" H
Shipping Weight	1148 lbs.
Electrical	220V, 60Hz, 15 amps, single phase (plug not included)