Choose the right HP Laminator for your home and business

HP laminators are fast, convenient and easy-to-use laminators designed to meet the needs of home, school & office environments. With a quick laminating speed of 24" per minute, our laminators are capable of accommodating documents up to 12" wide using 3 mil - 5 mil pouches. Quick warm-up times, from as little as 1 minute, HP laminators feature an auto sleep mode that activates after 60 minutes. Its ease of use and high quality of lamination makes it great for everyday laminating of photos, recipe cards, flash cards, menus, frequently used documents and much more.



9" Laminators







	HP 920	HP 940	
Entry size	9.17"	9.17"	
Rollers	2 rollers	4 rollers	
Lamination	Hot & Cold	Hot & Cold	
Warm-up time	2 - 3 minutes	1 minute	
Laminating speed (letter size)	29 seconds	31 seconds	
Hot pouch thickness	3 - 5 mil	3 - 5 mil	
Maximum laminating thickness (interlayer & pouch)	0.4 mm	0.5 mm	
Auto Sleep Mode	60 minutes	60 minutes	
Acoustic indication (beep):	Upon Start, Ready & Auto Sleep	Upon Start, Ready & Auto Sleep	
Optical indication (LED Flash):	Start, Ready & Auto Sleep	Start, Ready & Auto Sleep	
Continuous laminating	Yes	Yes	
Jam alert	No	Flashing REV button & constant beeping	
Jam release	Yes	Electric Forward & Reverse	
Starter kit included	(5) letter size, (3) 4x6 photo, (2) business card size	(15) letter size, (15) 4x6 photo, (20) business card size	
Voltage & rated current	120V 60HZ/ 600W	120V 60Hz/1050W	
Logistics Unit dimensions (LxWxH) Unit weight Box dimensions Box weight Quantity per master Master dimensions (LxWxH) Master weight	14.84" x 6" x 3.17" 3.96 lbs. 15.82" x 4.56" x 7.28" 4.4 lbs 6 16.34" x 14.25" x 15.2" 27.9 lbs	14.84" x 5.71" x 3.17" 5.28 lbs. 15.82" x 4.56" x 7.28" 6.3 lbs 4 16.34" x 9.69" x 15.2" 27 lbs	

12" Laminators







	HP 1220	HP 1240	
Entry size	12.87"	12.87"	
Rollers	2 rollers	4 rollers	
Lamination	Hot & Cold	Hot & Cold	
Warm-up time	2 - 3 minutes	1 minute	
Laminating speed (letter size)	29 seconds	31 seconds	
Hot pouch thickness	3 - 5 mil	3 - 5 mil	
Maximum laminating thickness (interlayer & pouch)	0.4 mm	0.5 mm	
Auto Sleep Mode	60 minutes	60 minutes	
Acoustic indication (beep):	Upon Start, Ready & Auto Sleep	Upon Start, Ready & Auto Sleep	
Optical indication (LED Flash):	Start, Ready & Auto Sleep	Start, Ready & Auto Sleep	
Continuous laminating	Yes	Yes	
Jam alert	No	Flashing REV button & constant beeping	
Jam release	Yes	Electric Forward & Reverse	
Starter kit included	(5) letter size, (3) 4x6 photo, (2) business card size	(5) letter size, (3) 4x6 photo, (2) business card size	
Voltage & rated current	120V 60HZ/ 600W	120V 60Hz/1050W	
Logistics Unit dimensions (LxWxH) Unit weight Box dimensions Box weight Quantity per master Master dimensions (LxWxH) Master weight	18.74" × 6.22" × 3.48" 5.06 lbs. 19.89" × 5.12" × 7.48" 6 lbs 4 20.47" × 10.83" × 15.75" 26.2 lbs	18.74" x 5.91" x 3.48" 7.72 lbs. 19.89" x 5.12" x 7.48" 8.7 lbs 3 20.47" x 15.94" x 8.27" 27.1 lbs	


Thermal Laminating Pouches





	S50	S100	S200
Size	Letter size	Letter size	Letter size
Actual pouch size	9" x 11.5"	9" x 11.5"	9" x 11.5"
Thickness	3 mil	3 mil	3 mil
Quantity	50	100	200
Color	Clear	Clear	Clear
Finish	Glossy	Glossy	Glossy
Logistics Box dimensions (LxWxH) Box weight Quantity per master Master dimensions (LxWxH) Master weight	0.39" x 9.17" x 11.65" 1.38 lbs. 20 18.9" x 12.28" x 4.72" 27.6 lbs	0.71" x 9.17" x 11.65" 2.76 lbs. 10 18.9" x 12.28" x 4.13" 27.6 lbs	1.26" x 9.17" x 11.65" 5.2 lbs. 6 in tray 10.83" x 8.66" x 12.2" 31.7 lbs





Distributed by

