

vivid.

MATRIX[®]

OMNI-FLOW

Matrix[®] Omni-Flow is a fully automated feeder, that is quick & easy to install, set-up and operate.



KEY FEATURES

- Retrofits to Matrix Pneumatic & Duplex Systems
- Quick & easy to set-up
- Fully automated lamination & foiling
- Change between paper stock in seconds

GREAT FOR USE IN

- Digital print shops
- Commercial printers
- Copy and print shops
- In-house print

IDEALLY SUITED FOR

- Foiling Prints
 - Business cards
 - Menus
 - Book covers
 - Brochures
 - Flyers
- and many more...

Specifications

Omni-Flow 520 (SRA2)

Max. paper Stack Height	500mm/19"
Paper Thickness (gsm)	160-350
Maximum Sheet Width	520mm/20"
Minimum Sheet Width	210mm/8"
Maximum Sheet Length	740mm/29"
Compatibility	MX-530P / MX-530DP **
Overall Dimensions WxDxH (mm/inches)	840x1100x1100/ 33x43x43
Weight (kg/lbs)	150/330
Power	1300W (220v 50/60Hz)
Warranty*	1 year

* For full terms & conditions on parts and labour warranty, visit vivid-online.com/support/warranty_information

** Maximum speed of Omni-Flow is determined by the maximum speed of the Matrix used

** Models from 2018

spiralbinding.com
800-631-3572

