

BINDING

# BQ-P65

## QUALITY BINDING WITH SIMPLE OPERATION.



Scan QR code  
and watch the  
product video.



### BENEFITS

#### EASY OPERATION


Simple operation panel with navigation indicator for easy operation.

#### FLEXIBLE BINDING STYLES


Choose from three different binding styles :  
Cover Binding, Tape Binding, Pad Binding.



Cover Binding



Tape Binding



Pad Binding

#### HIGH QUALITY

A cover is glued to the book spine and then clamped to create a quality bound book. The BQ-P65 applies a thinner glue film on the spine for higher quality padding.

#### OFFICE FRIENDLY OPERATION

An integrated odor extractor and filter system is a standard feature to clean the air and remove any glue odors from office environments.

#### ENERGY SAVING

Low-temperature glue and power saving mode to reduce energy consumption.

# PERFECT FOR BINDING MANUALS AND DOCUMENTS IN-HOUSE.

## CLAMPING SECTION

The book block is firmly clamped, to produce a professional quality book up to 25 mm (0.98") thickness.

## NIPPING SECTION

Nipping strength is adjusted automatically according to the binding style for a higher quality finish.



## COVER SECTION

Cover and tape can be applied to the spine. Tape widths of 30 mm to 40 mm (1.2" to 1.6") can be used.



## GLUING SECTION

Amount of glue can be adjusted depending on the thickness of the book with simple adjustment. Fume extractor removes glue odors for comfortable operation.



## OPERATION PANEL

Simple operation panel guides you through the binding process step by step.



## EASY OPERATION



1 Choose the binding style and insert the book block.



2 Press the start button.



3 Insert a cover (or tape), then press the start button.



4 The book is finished.

## CONSUMABLES.

### HM-302 GLUE

### ODOR ELIMINATING FILTER

### AIR FILTER



### PRINTABLE SPINE TAPE

### COLORED COVERS

- A4 / B5 size each 5 colors
- Cover for Laser Printer A4 size 2 colors

\*The machine design and specifications are subject to change without notice.  
\*Specifications may vary depending on the job, paper quality, environmental influences, and various other factors. Please do a test run before starting production.

## SPECIFICATIONS.

BQ-P65	
Binding Type	Cover Binding / Tape Binding / Pad Binding
Glue Type	Hot melt
Book Block Size	 <b>Spine Length x Fore-edge Length</b> Max. 315 x 210 mm or 12.4" x 8.2" Min. 210 x 148 mm or 8.3" x 5.9"
Book Block Thickness	Max. 25mm or 0.98"
Cover Size	 <b>Length x Width</b> Max. 315 x 445 mm or 12.4" x 17.5" Min. 210 x 297 mm or 8.27" x 11.70"
Cover Weight Range	82 to 210 gsm, 22 to 60 lb
Glue Temperature	130 to 150 degrees Celsius (266 to 302 degrees Fahrenheit)
Cycle Speed	22 seconds per cycle (Cover Binding)
Voltage / Frequency	Single Phase 115 V, 50 or 60 Hz Single Phase 220 to 240 V, 50 or 60 Hz
Rated Current	Single Phase 115 V, 50 or 60 Hz, 10 A Single Phase 220 to 240 V, 50 or 60 Hz, 5 A
Machine Dimensions	W600 x D615 x H270 mm or 23.7" x 24.3" x 10.7"
Machine Weight	48 kg or 106 lbs.