

L'Sealer/ Shrink Tunnel Combo

Model:

PP-1519 ECMC

Economical machine ideal for low to medium production.

New Design!
Featuring
"Micro Knife"
Technology



This compact **Model PP-1519 ECMC** L'Sealer with magnetic hold-down and power discharge conveyor with attached Tunnel is only 76" in total length. Featuring new "Micro Knife" technology - will seal PVC or Polyolefin Shrink Films. Tunnel features Live Roller Rod Conveyor with fully Re-Circulating Air Chamber, AC Variable Speed Conveyor, 0-60 FPM, Digital Temperature Control and Automatic Cool Down with Shut Off. A great machine for low to medium production speeds of 8-12 packages per minute. Available in 110 volts or 220 volts.

Model	POWER			Shipping Weight	Seal Dimensions W x L	Tunnel Dimensions L x W x H	Machine Dimensions L x W x H	Max Film Width	Production Rate
	Volts	Phase	Amps						
PP-1519ECMC SERIES	110	1	20	460 lbs.	15 x 19	20 x 16 x 6	76 x 26 x 50	22	8-12 PPM
	220	1	15						



Tunnel Control Panel



* *Shown with Optional PP 180-24 Gravity Curved Conveyor*

* *This machine is also available without the Magnet Hold-Down and Power Discharge at a Reduced Price*



Sealer Control Panel



Tunnel Features

- Fully Re-Circulating Air Chambers
- AC Variable Speed Drive, 0-60 FPM
- Live Roller Rod Conveyor
- Automatic Cool-Down with Shut-Off
- Digital Temperature Control 0° to 400°
- Anti-Jam Safety Feature on Conveyor

"Micro Knife" Technology

- Single Piece Teflon Band Ribbon with Round Corner Seal - Reduces Dog Ears
- Will Seal PVC or Polyolefin Shrink Film
- 1 Year Warranty on Band Ribbon
- Dual Magnet Hold Down & Power Discharge Conveyor

Pin Wheel Hole Punch

- Easy Load Film Rack
- Multiple Pin Wheels Provide Air Evacuation
- Adjustable Product Loading Tray