

## DATA SHEET

## GF NFD 248 3.0 MIL MATTE CLEAR FLEXIBLE CALENDERED VINYL FILM

GF NFD 248 is a 3.0 mil matte clear flexible calendered vinyl film which is coated with a permanent acrylic pressure sensitive adhesive and is laminated to a 90# lay flat liner. It is top coated with a cross-platform coating compatible with a wide array of narrow format production digital printing presses. The adhesive is a general purpose permanent adhesive that after 24 hours offers an excellent bond to many surfaces. The 90# poly coated liner maintains lay flat characteristics in a variety of ambient conditions. GF NFD 248 is available in a 19" x 13" sheet size.

| PRODUCT NAME  | GF NFD 248                         |
|---|------------------------------------|
| FILM  |                                    |
| Film Type   | Matte Clear Flex (Polymeric) Vinyl |
| Film Thickness (mils/µm)                                    | 3.0 / 80                           |
| Film Weight (gsm)   | 85                                 |
| Gloss (60°)   | < 20                               |
| ADHESIVE  |                                    |
| Adhesive Type   | Permanent                          |
| Adhesive Thickness (mils/µm)                                | 0.8-1.1 / 20-28                    |
| Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min | 3.2 / 14                           |
| Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs | 5.0 / 22                           |
| LINER   |                                    |
| Liner Weight (# / gsm)                                      | 90 / 145                           |
| Liner Type  | White PE Coated Kraft              |
| Liner Thickness (mils / µm)                                 | 6.7 / 170                          |
| Release Force @ 300" / min (g/2")                           | 90-140                             |
| TOTAL CONSTRUCTION  |                                    |
| Thickness (mils / microns)                                  | 11 / 274 (+/- 10%)                 |
| Weight (# per 3000ft² / gsm)                                | 163 / 265                          |
| PERFORMANCE GUIDANCE  |                                    |
| Application Temperature                                     | >+40°F                             |
| Service Temperature   | -40°F to +180°F                    |
| Shelf Life  | 1 Year                             |
| Storage Temp / Rel. Humidity                                | 70°F / 50% RH                      |
| Outdoor Durability  | 5 Years                            |

