

# Adhesive Backed 3 mil Gloss White Vinyl Gray Permanent Adhesive for Solvent, Latex & UV Printers

- Designed for slightly textured exterior asphalt and cured concrete surfaces
- Use with slip-resistant outdoor floor laminate - KJ5FLRLAM
- Outdoor life up to 60 days with lamination
- Uses include outdoor signage, promotional and point of purchase graphics
- Compatible with OEM Solvent, Latex & UV Curable Inks

## Construction

Product Number:	SOL/SIDEWALK
Adhesive:	4 mil Permanent Acrylic
Film:	3 mil Vinyl
Liner:	90# Polycoated two sides
Finish:	Gloss White
Gloss Level:	85 (avg.) @ 60°

## Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Date represents averages and is not intended for use as a specification.)

Durability:	Outdoor -5 years unprinted	
Minimum Application Temperature:	+50° F (Minimum for Substrate)	
Service Temperature Range:	-40° F to +180° F	
Chemical Resistance:	Resistant to alkalies, mild acids, most petroleum based oil, grease and aliphatic solvent and salts.	
Typical Adhesion Values:	180° Peel Test	
	<u>Substrate</u>	<u>24 hrs.</u>
	Stainless Steel	7.5 lb/in
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity	