

### FEATURES & BENEFITS

- User friendly operator controls for fast, easy & repeatable set up
- Quick height adjustment facilitates centering the seal on product
- Digitally controlled tunnel temperature with heavy-duty blower provides 360 degree air circulation for consistency and maximum performance
- Seal temperature control provides repeatability of seal performance
- Dwell control provides additional flexibility for utilizing a wide range of films
- Heavy duty magnetic hold down to insure consistent seal pressure
- Film cradle can accommodate up to 20" wide roll of film
- Automatic cool down and shut off ensure maximum component reliability
- Adjustable airflow and variable tunnel conveyor speed to maximize shrink performance
- Adjustable unitized package tray and film cradle with pinwheel perforator
- Tunnel curtain design minimizes heat loss & maintains tunnel temperature consistency
- Robust design with a welded steel frame & heavy duty steal arm
- Designed to meet CE requirements

### OPTIONS & ACCESSORIES

- Power take-away conveyor
- Variable speed power take-away conveyor
- 12" opening tunnel (220 Combo only)
- Short frame (74" long)
- 2" seal bar extension

User friendly set up



Magnetic hold-down feature



Adjustable workshelf height



Seal Area



The **Clamco Combo** shrink system combines the L-Bar sealer and shrink tunnel for packing, sealing, and shrinking products. The sealer and tunnel share a common heavy duty frame and base which allows for quick set up, alignment, and product transfer between the sealer and the tunnel.

The Clamco Combo system includes standard features such as a film cradle with a pinwheel perforator and a unitized package tray to assist in the fast and efficient placement of the product into the film.

The sturdy design of the Combo provides the framework for greater productivity and insures consistently strong seals. The use of integrated application specific controls allow for easy and fast operator set up and provides for years of trouble free operation.

### SPECIFICATIONS:

Film Capacity	20" wide (508mm)
L-Bar Seal Area	16"W x 20"L (406mm x 508mm)
Maximum Product Height	6" (152mm)
Tunnel Chamber Dimensions	16"L x 20"W x 8"H (406mm x 508mm x 203mm)
Machine Dimensions	24"L x 91"W x 52"H (610mm x 231mm x 1321mm)
Machine Weight	480lbs (168kg)
Electrical Requirements (120 Combo)	120V, 20 amp, 50/60Hz, 2,400w
Electrical Requirements (240 Combo)	220V, 25 amp, 50/60Hz, 4,000w