

DEMPACK™ H20 & H25


DEMPACK H20 & DEMPACK H25

The **Dempack H20** and **H25** are single step machines incorporating seal, trim and shrink into a single operation. These unique chamber style shrink systems operate with a shrink hood instead of a tunnel. The hood is pressed down manually for seal pressure, closure is then maintained by an electronic hold-down magnet during the seal and shrink operations.


These shrink systems are designed for simple maintenance and quiet operation. In fact, no custom installation is required. The **Dempack** has an excellent seal quality and long lifetime, compared to similar machines on the market. Its compatibility with most shrink films, combined with its space saving size, make this unit ideal for many industries.

FEATURES & BENEFITS

- Easy to program and operate
- Easy to adjust work surface for fast changeover from job to job
- L-sealer and heat tunnel combined into a single unit to reduce machine footprint
- Film perforation wheel relieves pressure and 'pillowing' effect from heat shrinking process
- Magnetic hold-down feature during complete machine cycle



Quick and easy loading



Magnetic hold-down feature



User friendly set up

SPECIFICATIONS

	DEM-H20	DEM-H25
Average Output / Hour	200-300	200-300
Seal Bar Size	17" x 12" (440 X 300mm)	22" x 17" (600 X 430mm)
Maximum Product Height	8-1/4" (210mm)	10-1/4" (260mm)
Machine Dimensions	48.5"L x 27"W x 52" H (123 x 68 x 131cm)	60"L x 31"W x 56"H (152 x 78 x 143cm)
Shipping Size	44"L x 27"W x 27"H (111 x 68 x 69cm)	59"L x 34"W x 31"H (149 x 86 x 78cm)
Machine Weight	190 lbs (88 kg)	340 lbs (153 kg)
Electrical Requirements	220VAC, 50/60Hz, 2,300w	220VAC, 50/60Hz, 3,600w