

ALM3222 Automatic Laminator

FEATURES & BENEFITS

- Heated rollers for crystal clear scratch free laminations
- Adjustable Flush or Sealed edge trim option micro adjustable for precise flush cut or custom encapsulation
- Now handles up to 13" wide sheets (12.6" of film coverage)
- Built-in long mode operation for banner length prints
- 25% increase in speed over the ALM3220
- Small foot print - less than 4 sq. ft.
- Portable with locking roller casters
- 120 Volt, 15 amp service with economy mode
- Ultra quick warm up of less than 5 minutes
- Virtually unattended operation
- Digital Sheet Sizes: 13" x 19", 12" x 18", 11" x 17", 8.5" x 11"
- Operating with built-in long mode allows sheets of infinite length to be laminated
- Automatically feeds up to 200 sheets
- Laminates copy paper or as heavy as 130# cover stock
- Automatic two side lamination or short one side work
- Small foot print - less than 4 sq. ft.
- 1 year parts and 90 day labor warranty



The next generation in fully automatic laminating of digital prints, the all new **ALM3222** offers many upgrades from the original ALM3220.

What remains the same is the easy "green button" operation that provides virtually labor free laminated and trimmed sheets. Excellent adhesion to even the most difficult digital prints with the same ASAP adhesive films pioneered on the ALM3220.

ALM Exclusive ASAP Roll Film

- Perfect for Digital Print Technology
- Anti-static properties

OTHER FEATURES

- Laminated Sheet Counter
- Paper Thickness Adjustment Lever
- Automatic stop at end of film
- Emergency Stop Function
- Film Tension Control
- Power Saving Mode
- Roller Gap Lever

ALM Exclusive ASAP Roll Film

- 1.5mil, 12.6" x 984 ft, Gloss / Matte
- 3.0mil, 12.6" x 492 ft, Gloss / Matte
- 5.0mil, 12.6" x 328 ft, Gloss / Matte
- 10.0mil, 12.6" x 165 ft, Gloss Only*
- 1.2mil, 12.6" x 984 ft, Nylon (Gloss / Matte Versions)

**The use of 10mil film is limited to border cut only.*

**Do not use 10 mil film with flush cut applications.*

SPECIFICATIONS:

Laminating Speed	20" - 68" / min.
Temperature Range	170 - 270° F
Ultra Fast Warm-Up Time	Approximately 5 minutes
Film Thickness	1.2 mil (one-sided application), 1.5, 3, & 5mil, ASAP Roll Film
Thickness of Objects	20lb. bond - 130lb. cover
Paper Feeding	Capacity - 200 sheets, Adjustable Paper Guide
Trimming Methods	2 modes - flush trim or edge seal for all 4 sides of the print
Operation Panel	LCD display for start, stop, temperature speed, and trim settings, leading and trailing edge side cuts are adjustable
Weight	130 lbs. (laminator) / 48.5 lbs. (stand)
Power	900W / AC 120V (60Hz)
Included Accessories	Stand with film waste, box, Printed operations manual
Applicable Sizes:	Letter (8.5" x 11"), Tabloid (11" x 17"), Digital Paper (12" x 18"), Paper (13" x 19")



800-631-3572
spiralbinding.com